



Technical Data Sheet

PRODUCT NAME	Aspira Mould Remover
ISSUE DATE	4 th August 2014
ISSUED BY	Michael McNicholas
PRODUCT CODES	AAREM-500 and AAREM-5L
PRODUCT DESCRIPTION	<p>Aspira Mould Remover is a premium quality water-based cleaner for application on all walls susceptible to microbial growth.</p> <p>Aspira Mould Remover offer outstanding properties such as excellent durability, ease of use and exceptional protective qualities.</p> <p>Aspira Mould Remover has been independently tested to prove Anti-Bacterial (EN1276), Anti-Algal (ASTM 5589) and Anti-Mould (ASTM 5590).</p>
DIRECTIONS	<p>To avoid spreading the spores, pour liquid onto a disposable cloth and apply generously to the wall removing the mould. Ensure that the surface is thoroughly wetted to kill residual growth. Allow to dry and then repeat the process until the surface contamination is fully removed, although some staining may still remain.</p>
MAXIMUM VOC CONTENT (RFU)	10 VOC g/l
COLOUR RANGE	Clear Liquid
PACKING	500ml aluminium screw cap 5 Litre HDPE Jerry Can with tamper-proof screw cap
COVERAGE	Approx. 10 square metres per litre dependant on substrate.
FLASHPOINT	Not applicable

STORAGE	Keep in a dry safe, well-ventilated place between 5°C and 30°C. Keeps for 12 months in original, unopened, containers
CLEANING	Use warm soapy water to clean any brushes or rollers and to clean any spillage.
HEALTH AND SAFETY	Refer to Material Safety Data Sheet.
Number of applications One application is usually sufficient; however, if the substrate is particularly porous, then an additional application can be applied once dry	
Drying Time Dependent on the temperature and porosity of substrate 4 hours minimum @20°C to be touch-dry.	
Technical Support	0161 262 2112
Preservation Paints Riverside Works Collyhurst Road Manchester M40 7RU, UK www.preservationpaints.com	