



Technical Data Sheet

PRODUCT NAME	Aspira Mould Repellent
ISSUE DATE	4 th August 2014
ISSUED BY	Michael McNicholas
PRODUCT CODES	AMREP-500 and AMREP-5L
<p>PRODUCT DESCRIPTION Aspira Mould Repellent is a premium quality transparent coating for application on all walls susceptible to microbial growth.</p> <p>Aspira Mould Repellent offer outstanding properties such as excellent durability, ease of use and exceptional repellent and protective qualities.</p> <p>Aspira Mould Repellent has been independently tested to prove Anti-Algal (ASTM 5589) and Anti-Mould (ASTM 5590)</p>	
<p>DIRECTIONS Make sure surface is clean and dry. Apply using a cloth, brush or roller. Allow to dry, protecting from water and cold conditions for 12 hours after application. One coat only is required.</p>	
MAXIMUM VOC CONTENT (RFU)	723 VOC g/l
<p>REGULATIONS / COMPLIANCE Non Persistent Bioaccumulative and Toxic under the USA Environmental Protection Agency's PBT Chemical policy</p>	
COLOUR RANGE	Clear/yellow Liquid
PACKING	500ml aluminium screw cap 5 Litre Lever Lid Tin
COVERAGE	Approx. 10 square metres per litre dependant on substrate.
FLASHPOINT	68°C

STORAGE	Keep in a dry safe, well-ventilated place between 5°C and 30°C. Keeps for 12 months in original, unopened, containers
CLEANING	Use White Spirit to clean any brushes or rollers and to clean any spillage.
HEALTH AND SAFETY	Refer to Material Safety Data Sheet.
Number of applications One application is usually sufficient; however, if the substrate is particularly porous, then an additional application can be applied wet on wet.	
Drying Time Dependent on the temperature and porosity of substrate 12 hours minimum @20°C to be touch-dry.	
Technical Support	0161 262 2112
Preservation Paints Riverside Works Collyhurst Road Manchester M40 7RU, UK www.preservationpaints.com	